



1 型号 — 公差选择 — 2 D — 3 V — 4 D — 5 V — 6 T
ECSC — **G** **H** — **D10.0** — **V4.0** — **T1.0**

■ 请按步骤①~⑥选择型号和参数后进行订购。



型号区分: **7** 天发货
 代码

■ 普通级

型号	材质	表面处理
ECSC	S45C	—
ECSWB		发黑
ECSWM		无电解镀锌
ECSWS	SUS304	—

D	D公差选择			
	G g6	H h7	N —	X —
5.0~8.5	—	—	—	—
9.0~10.0	-0.005	0	-0.1	0
	-0.014	-0.015		
10.5~18.0	-0.006	0	-0.3	-0.2
	-0.017	-0.018		
18.5~30	-0.007	0	—	—
	-0.020	-0.021		
31~50	-0.009	0	—	—
	-0.025	-0.025		
51~60	-0.010	0	—	—
	-0.029	-0.030		

V	V公差选择			
	H H7	N —	X —	—
3.0	+0.010	—	—	—
	0			
3.5~6.0	+0.012	—	—	—
	0			
6.5~10.0	+0.015	—	—	—
	0			
10.5~18.0	+0.018	+0.3	+0.1	+0.2
	0			
18.5~30.0	+0.021	—	—	—
	0			
30.5~50.0	+0.025	—	—	—
	0			
50.5~58.0	+0.030	—	—	—
	0			

1 型号	2 D公差选择	3 V公差选择	4 D	5 V 最小单位 0.5mm	6 T 最小单位 0.1mm
ECSC ECSWB ECSWM ECSWS	G H N X	H N X	5.0~10.0 单位0.5mm	3.0~58.0 (V≤D-2)	1.0~2.9
			10.5~20.0 单位0.5mm		3.0~5.0
			21~30 单位1mm		5.1~10.0
			31~40 单位1mm		1.0~2.9
			41~50 单位1mm		3.0~5.0
			51~60 单位1mm		5.1~10.0

① ECSC型T≥3 ② D·V公差选择了G或H时, 适用D≥9。此时, V的指定范围如下表所示。

D	V	T
9~30	D-V≥6	1~10
31~60	D-V≥12	2~10



1 型号 — 公差选择 — 3 D — 5 V — 6 T — (TCB·TCC·TCD·TCE)

ECSC — **G** **H** — **D10.0** — **V4.0** — **T1.0** — **TCB**

变更普通级公差	可选加工	变更负公差	变更正公差	变更零·负公差	变更零·正公差
	代码	TCB	TCC	TCD	TCE
<p>① 普通级适用</p>	变更厚度公差(T)	变更厚度公差(T)	变更厚度公差(T)	变更厚度公差(T)	
	T -0.1 T -0.3 指定方法 TCB	T +0.3 T +0.1 指定方法 TCC	T 0 T -0.2 指定方法 TCD	T +0.2 T 0 指定方法 TCE	



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD 仕瑞达