



型号(1代码·2M)
EAHTC3

■请按步骤1~2选择
型号和参数后进行订购。





型号区分:
代码 **7** 天发货

■ 自攻307标准型



代码	类型			材质	表面处理	用途
EAHTC	自攻307标准型	三圆孔型	粗牙	碳素钢	镀彩锌	加强螺纹强度
EAHTD				SUS303	—	





型号		P 螺距	L	N 外螺纹	参考钻孔直径		最小 钻孔深度	参考重量 (g)
1 代码	2 M				铸铁	铝合金		
EAHTC EAHTD	3	0.5	4	M5×0.6	4.7~4.8	4.6~4.7	6	0.3
	4	0.7	6	M6.5×0.8	6.1~6.2	6.0~6.1	8	0.8
	5	0.8	7	M8×1.0	7.6~7.7	7.4~7.5	9	1.3
	6	1	8	M10×1.25	9.5~9.6	9.3~9.4	10	2.4
	8	1.25	9	M12×1.5	11.3~11.5	11.1~11.3	11	3.2
	10	1.5	10	M14×1.5	13.3~13.5	13.1~13.3	13	4.5
	12	1.75	12	M16×1.75	15.3~15.5	15.0~15.3	15	6.4

■ 自攻308加强型



代码	类型			材质	表面处理	用途
EAHTV	自攻308加强型	三圆孔型	粗牙	碳素钢	镀彩锌	加强螺纹强度
EAHTW				SUS303	—	



型号		P 螺距	L	N 外螺纹	参考钻孔直径		最小 钻孔深度	参考重量 (g)
1 代码	2 M				铸铁	铝合金		
EAHTV EAHTW	3	0.5	6	M5×0.6	4.7~4.8	4.6~4.7	8	0.45
	4	0.7	8	M6.5×0.8	6.1~6.2	6.0~6.1	10	1
	5	0.8	10	M8×1.0	7.6~7.7	7.4~7.5	13	1.85
	6	1	12	M10×1.25	9.5~9.6	9.3~9.4	15	4
	8	1.25	14	M12×1.5	11.3~11.5	11.1~11.3	17	5.4
	10	1.5	18	M14×1.5	13.3~13.5	13.1~13.3	22	8
	12	1.75	22	M16×1.75	15.3~15.5	15.0~15.3	26	12.5



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRO 仕瑞达