



齿轮/齿条



直齿轮

压力角20° 模数0.8



型号(①代码·②模数)

CFAHBB0.8

③齿数

20

④厚度B

5

⑤齿轮形状

A

⑥轴径

6

■ 请按步骤①~⑥选择型号和参数后进行订购。



型号区分:

代码

7 天发货


■ A形状



代码	材质	表面处理
圆孔		
CFAHBN	S45C	—
CFAHBB		发黑
CFAHBG		无电解镀镍
CFAHBS	SUS304	—



⑤ A形



① 未指定齿轮形状时, 齿数12~15为K形状, 齿数16~50为B形状。

型号		③齿数	④厚度B	⑤齿轮形状	⑥轴孔直径PH7 最小单位1mm	d 基准圆直径	D 齿顶圆直径	G 齿根圆直径	
① 代码	② 模数								
圆孔 CFAHBN CFAHBB CFAHBG CFAHBS	0.8	16	5	A	4~6 · 6.35	12.8	14.4	10.8	
		16	7			14.4	16	12.4	
		18	5			16	17.6	14	
		18	7						
		20	5						
		22	7						
		24	5		5~8 · 6.35	19.2	20.8	17.2	
		24	7			20	21.6	18	
		25	5						
		25	7			24	25.6	22	
		30	5			25.6	27.2	23.6	
		30	7			28.8	30.4	26.8	
		32	5		6~9 · 6.35	32	33.6	30	
		36				36	37.6	34	
		40				40	41.6	38	
		45							
		50							



型号(①代码·②模数)

CFAHBB0.8

③齿数

20

④厚度B

5

⑤齿轮形状

A

⑥轴径

6

(etc)

可选加工	台阶孔	两端台阶孔	侧面腰形孔
代码	DHL · DHR	WDH	LFC · LTC
技术说明	初始B形状 (可为A形) 	初始A形状 	LFC(腰形孔4处) 30° R=C/2 LTC(腰形孔3处) 30° R=C/2
可选加工	侧面通孔	侧面螺纹孔	侧面沉孔
代码	KFC · KTC	QFC · QTC	ZFC · ZTC
技术说明	KFC(通孔4处) KTC(通孔3处) 	QFC(螺纹孔4处) QTC(螺纹孔3处) 	(4处) ZFC (3处) ZTC

