

新增

免键轴衬  
简易型·带定心功能

同步轮/同步带/免键轴衬



型号(①代码·②d)  
CBLC19

■ 请按步骤①~②选择型号和参数后进行订购。





型号区分:  
代码 5 天发货



■ 推荐安装尺寸:  
轴: h8  
毂: H8

① 类似JB/T7934-1999 CSF-A8型免键轴衬




代码	类型		材质	表面处理
CBLC	简易型	带定心功能	S45C	—
CBLCP				无电镀锌镍

※ 拆卸用螺孔的螺径与锁紧螺栓相同。

型号		D	D <sub>1</sub>	L <sub>1</sub>	L <sub>2</sub>	L <sub>3</sub>	L	传递的轴向力 F <sub>t</sub> (KN)	传递扭矩 M <sub>t</sub> (Nm)	接触面压强		DIN912-12.9级锁紧螺钉		
① 代码	② d									轴	毂	数量	规格	锁紧扭矩 Ts(Nm)
CBLC CBLCP	19	47	56	17	22	28	34	26	243	234	94	5	M6×20	17
	20								256	222				
	22								282	202				
	24	50	59					31	368	222	106			
	25								383	213				
	28								429	190				
	30	55	64	41	460	177	97							
	32				655	222								
	35				716	203								
	38	60	69	8	778	187	109							
	40				819	178								
	42				75	84		65	1361	227	127			
	45	1458	212											
	50	1620	191											
	55	80	89	74	2037	199	129							
	60				2223	182								
65	2710				189									
70	95	104	83	4203	211	134								
75				4754	197									
80				4804	184									
75	115	124	24	30	40	50	120	4754	197	128	8	M10×30	83	
80								4804	184					

使用示例



同步轮·同步带  
免键轴衬

15



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达