

■圆型



■方型

■简易型

6.3/(1.6/)

d3~17

d20~30



① 无扣环型轴承有脱落可能, 重新安装后可正常使用。

型号(①代码·②轴承型号·③密封圈) — ④ L
BBHC6200ZZ — 30

■请按步骤①~④选择型号和参数后进行订购。



型号区分: 7 天发货

① 代码	② 轴承型号	③ 密封圈	④ L 选择	d	Dh7	公差	B	H	W	T	dh	D197	公差	P.C.D.	K	A	F	d1	d2	H1	可订购型号
(圆型)	623	ZZ (双盖式)	20 30	3	10	+0.015 0	4	33	16	7	7	14	-0.006 -0.024	24	27	24		6.5	3.5	3.1	BBFCB BBFC BBAFC BBSAFC BBSFC
	624		20 30	4	13		5	35	18		9	17		26	28	26					BBKCB BBKC BBAKC BBSAKC BBSKC
	605		20 30	5	14	+0.018 0	5	36	20		10	18		26	30	26					BBAHC BBSAHC BBSHC
	625		25 30		16		5	38	22		12	20		28	31	28					
	606		20 35		17		6	39	23		13	21	-0.007 -0.028	29	32	29					
	626		25 35	6	19	+0.021 0	6	41	25		15	24		31	34	31					
	678		20 30		12	+0.018 0	3.5	34	18		10	16	-0.006 -0.024	25	27	25		6.5	3.5	3.1	
	698		25 35		19		6	41	25		15	24		31	34	31					
	608		25 35		22	+0.021 0	7	45	29		18	27		35	36	35					
	628		25 35		24		8	47	32		20	30	-0.007 -0.028	37	37	37					
	6700		20 30		15	+0.018 0	4	37	22		12	19		27	30	27					
(方型)	8800	VV (非接触式橡胶密封圈)	20 30		19		5	41	25		15	24		31	34	31					
	8900		25 40		22	+0.021 0	6	45	29		19	27		35	36	35					
	6000		25 40		26		8	50	34		22	32	-0.009 -0.034	40	39	40					
	6200		30 40		30		9	54	38		24	36		44	42	44					
	6701		20 30		18	+0.018 0	4	40	25		15	23	-0.007 -0.028	30	31	30					
	6801		25 35		21		5	44	29		17	26		34	35	34					
	6901		25 40		24	+0.021 0	6	48	31		21	30		38	38	38					
	6001		25 40		28		8	52	36		24	34	-0.009 -0.034	42	40	42					
	6201		30 40		32	+0.025 0	10	56	40		26	38		46	43	46					
	6702		25 35		21		4	44	29		18	26	-0.007 -0.028	34	35	34					
	6802		25 35		24	+0.021 0	5	47	32		20	30		37	37	37					
	6902		25 50		28		7	57	37		25	35		45	45	45					
(简易型)	6002	DD (接触式橡胶密封圈)	30 50		32	+0.025 0	9	60	40		28	38		48	46	48					
	6202		35 50		35		11	64	44		29	42		52	49	52					
	6803		30 40		26	+0.021 0	5	50	34		22	32		40	39	40					
	6903		30 40		30		7	60	38		27	36	-0.009 -0.034	48	46	48					
	6003		35 50		35	+0.025 0	10	66	44		31	42		54	50	54					
	6203		40 50		40		12	72	50		34	48		60	54	60					
	6704		30 40		27	+0.021 0	4	51	35		23	33		41	39	41					
	6804		35 50		32		7	60	40		28	38		48	46	48					
	6904		35 50		37		9	69	47		34	45	-0.010 -0.040	56	54	56					
	6004		40 50		42		12	77	54		36	50		64	59	64					
	6204		45 50		47	+0.025 0	14	81	58		40	54		68	62	68					
	6805		35 50		37		7	69	47		34	45	-0.009 -0.034	56	54	56					
(双盖式)	6905	ZZ (双盖式)	35 50		42		9	77	54		36	50	-0.010 -0.040	64	59	64					
	6005		40 60		47		12	88	58		41	54		72	67	72					
	6205		45 60		52	+0.030 0	15	94	64		45	60	-0.010 -0.040	78	72	78					
	6806		35 50		42	+0.025 0	7	77	54		36	50	-0.009 -0.034	64	59	64					
	6906		35 50		47		9	88	58		41	54		72	67	72					
	6006		40 60		55		13	96	66		48	62	-0.010 -0.040	80	73	80					
	6206		50 60		62		16	104	74		55	70		88	79	88					
	6007		50 60		62		14	104	74		55	70		88	79	88					
	6207		60 80		72	+0.030 0	17	126	88		64	84	-0.012 -0.047	105	95	105					
	6008		60 70		68		15	114	82		60	78	-0.010 -0.040	96	86	96					
	6208		70 80		80		18	134	96		74	92		113	102	113					
	6010		70 80		80		16	134	96		74	92	-0.012 -0.047	113	102	113					
	6210		90		90	+0.035 0	20	147	110		83	106		126	113	126					

型号(①代码·②轴承型号·③密封圈) — ④ L — (NA)
BBSHC6200ZZ — 30 — NA

可选加工

代码

技术说明

不装配轴承

NA

不将轴承装入固定座中, 而以附件形式发货。



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达