09

支撑侧▶

滚珠丝杠/支座组件







■请按步骤①~❷选择型号和参数后进行订购。










(1) ZTI	- N	-#I	材质	表面处理			
1 C11=3	<u> </u>	: **	1 3	1			
AIUN	经济型	支撑侧	S50C	发黑			


- ① 轴承已经封入适量锂皂基抗极压润滑脂。
- ①轴承为双铁盖。


d25

①使用JIS 5级的深沟球轴承、最适用于高精度、 高速旋转用途。


撑侧		S50C	发黑						
	编号	号 零件名称							
	1	轴承座本位	1						
	2	深沟球轴承	深沟球轴承 5级						
	3	C型挡圈		1					








■ 建议轴端加工尺寸





型号														建议轴端加工尺寸							
代码 规格		Ød	L	В	Н	h	B ₁	H ₁	Р	Ød1	Ød2	t	N	搭配丝杠轴径	轴端部外径	1	挡圈沟	槽尺寸		使用 C型挡圈	
	规恰					0-0.02							±0.02	ØD	Ød	ØA	Е	F	G		
AIUNA	6	6	12	42	25	13	18	20	30	5.5	9.5	11	21	8	6-0.005	5.7	9	6.8	0.8	- 1 OWN 10	
	8	6	14	52	32	17	25	26	38	6.6	11	12	26	8/10						EASWN6	
	10	8		70	43	25	36	35			9 14	11	35	12/14/15	8-0.005 -0.012	7.6	10	7.9	0.9	EASWN8	
	12	10	20						52	9				14/15/16	10 -0.005	9.6	11	9.15	4.45	EASWN10	
	15	15		80	50	30	41	40	60	9			40	18/20	15 -0.005	14.3	13	10.15	1.15	EASWN15	
	20	20	26	95	58		56	45	75	11	17	15	47.5	25/28/30	20 -0.005	19	19	15.35	1.05	EASWN20	
	25	25	30	105	68	35	66	25	85	11	-	-	52.5	28/30/32	25 -0.005	23.9	21	16.35	1.35	EASWN25	

