



1 代码 2 D — 3 公称型号  
FFJBC6— 2

■ 请按步骤 1~3 选择型号和参数后进行订购。



型号区分: 代码 5 天发货

■ 三通压合接头 **FFCTPT**

材质 SUS316

型号		螺纹尺寸 R (PT)	适用气管 外径 (mm)	适用管 内径 (mm)	L <sub>1</sub>	L <sub>2</sub>	A	B	对边间距									
1 代码	2 No.								H <sub>1</sub>	H <sub>2</sub>								
FFCTPT	4-1	1/8	4	2.5	20	18	9	6	12	10								
	4-2	1/4																
	6-1	1/8	6	4	21.5	18	11	6	14	10								
	6-2	1/4																
	8-15	1/8	8	5	23.5	19	9	7.5	14	14								
	8-1	1/8																
	8-2	1/4																
	8-3	3/8																
	8-36	3/8																
	10-2	1/4																
	10-36	3/8	10	6.5	28.5	26	12	8	22	17								
	10-3	3/8																
	12-28	1/4									12	8	30	26	11	9.5	22	19
	12-2	1/4																
12-3	3/8	12	10	30	27	12	9.5	22	19									

■ 三通压合接头 **FFCUT**

材质 SUS316

型号		适用气管 外径 (mm)	适用管 内径 (mm)	L	B	对边间距	
1 代码	2 No.					H <sub>1</sub>	H <sub>2</sub>
FFCUT	4	4	2.5	20	6	12	10
	6	6	4	21.5	7	12	12
	8-5	8	5	23.5	7.5	14	14
	8	8	6	23.5	7.5	14	14
	10	10	8	28.5	8	22	17
	12-8	12	8	30	9.5	22	19
	12-9	12	9	30	9.5	22	19
12	12	10	30	9.5	22	19	

■ 直立压合接头 **FFJBC**

材质 黄铜

型号		适用气管 外径 D (mm)	公称型号	气管内径 (mm)	L	L <sub>1</sub>	B	H <sub>1</sub>	H <sub>2</sub>	T R (PT)	重量 (g)
1 代码	2 No.										
FFJBC	6	1	1	4	26	22	12.5	12	12	R1/8	18
					28.5	22.5		14	12	R1/4	26
	8	1	1	5	28	24	14	14	14	R1/8	25
					30	24		14	14	R1/4	30
	10	2	2	6.5	31	24.6	15.5	17	14	R3/8	41
					32	26		17	17	R1/4	43
	12	3	3	8	33	26.6	17	17	17	R3/8	50
					34	28		17	19	R1/4	49
					35	28.6		17	19	R3/8	57

