



型号(1代码) — (2A) — (3H) — (4T)
DBGLB — 20 — 10 — 15

■ 请按步骤①~④选择型号和参数后进行订购。



型号区分: 7天发货
代码



■ 特长: 外形最适用于工件定位。

■ L型



代码		材质	硬度	表面处理
紧凑型	标准型			
DBGLBC	DBGLB	S45C	—	发黑
DBGLMC	DBGLM			无电解镀锌
DBGLSC	DBGLS	SUS304		—
DBGLJC	DBGLJ	聚缩醛		—
DBGLNC	DBGLN	MC尼龙	38HRC~	发黑
—	DBGDCH	S45C		无电解镀锌
—	DBGECN	A2017	—	—
—	DBGFL			—

$\sqrt{25} / (\sqrt{6.3} / \sqrt{1.6})$



① 代码	② A选择	③ H最小单位 1mm	④ T	h	X	Y	d1	d2	ℓ
(紧凑型) DBGLBC DBGLMC DBGLSC DBGLJC DBGLNC	17 20	6~10	10	H-3	4.5	4.5	6.5	3.5	3.5
	20 30		12		4.5	4.5	6.5	3.5	3.5
(标准型) DBGDCH DBGECN DBGFL DBGLB DBGLM DBGLS DBGLJ DBGLN	20 30 40 50	10~30	12	H-5	5	5	6.5	3.5	3.5
	20 30 40 50		15		5	6	8	4.5	4.5
	30 40 50 60		20		7	9	9.5	5.5	5.5
	30 40 50 60	15~30	25		8	11	11	6.5	6.5
	40 50 60		30		11	14	14	9	9



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达