



型号(①代码·②D) - ③T
CDGB15 - 6

■ 请按步骤①~③选择型号和参数后进行订购。



型号区分 代码 7 天发货




代码		材质	表面处理	材质	附件
法兰型	圆弧型	S45C	发黑	钢	挡圈 (SUS304)
CDGB	CDGC		无电解镀锌		
CDGM	CDGCM	铝合金	本色阳极氧化处理		
CDGA	CDGCA				
CDGMS	CDGMS	SUS304	-	不锈钢	

④ 蓝底为新增

法兰型

T=6·11



T=16·21·27·32



圆弧型

T=11



T=16·21·27·32



① T的公差精度为±0.2, 请确认平皮带宽度公差后选择惰轮型号。

型号 ①代码	②D	③T	P	dh	l	L	使用轴承					
							No.	d	B			
法兰型 CDGB CDGM CDGA CDGMS	6	11	11	9	2	8	694ZZ×1	4	4			
			20	16	13	1.5	8	625ZZ×1	5	5		
	11	16	20	16	13	4	13	625ZZ×1	5	5		
			25	19	16	3.5	13	626ZZ×1	6	6		
			30	19	17	3.5	13	698ZZ×1	8	6		
			15	11	9	-	18	685ZZ×2	5	5		
	16	20	20	16	13	-	18	625ZZ×2	5	5		
			25	19	16	-	18	626ZZ×2	6	6		
			30	19	17	-	18	698ZZ×2	8	6		
			35	26	23	-	18	6000ZZ×2	10	8		
			40	26	23	-	18	6000ZZ×2	10	8		
			21	20	15	11	9	-	23	685ZZ×2	5	5
					20	16	14	-	23	688ZZ×2	8	6
					25	19	17	-	23	698ZZ×2	8	6
	30	19			17	-	23	698ZZ×2	8	6		
	27	20	35	26	23	-	23	6000ZZ×2	10	8		
			40	28	25	-	23	6001ZZ×2	12	8		
			15	11	9	-	29	685ZZ×2	5	5		
			20	16	14	-	29	688ZZ×2	8	6		
			25	19	17	-	29	698ZZ×2	8	6		
30			19	17	-	29	698ZZ×2	8	6			
40			26	23	-	29	6000ZZ×2	10	8			
50			28	25	-	29	6001ZZ×2	12	8			
32	20	15	11	9	-	34	685ZZ×2	5	5			
		20	16	14	-	34	688ZZ×2	8	6			
		25	19	17	-	34	698ZZ×2	8	6			
		30	19	17	-	34	698ZZ×2	8	6			
		40	26	23	-	34	6000ZZ×2	10	8			
		50	28	25	-	34	6001ZZ×2	12	8			

型号 ①代码	②D	③T	P	dh	l	L	使用轴承				
							No.	d	B		
圆弧型 CDGC CDGCM CDGCA CDGMS CDGCAP	6	11	20	16	16	3	13	625ZZ×1	5	5	
			25	19	19	2.5	13	626ZZ×1	6	6	
	11	16	30	19	19	2.5	13	698ZZ×1	8	6	
			15	11	11	-	18	685ZZ×2	5	5	
			20	16	16	-	18	625ZZ×2	5	5	
			25	19	19	-	18	626ZZ×2	6	6	
	16	20	30	19	19	-	18	698ZZ×2	8	6	
			35	22	17	-	18	6900ZZ×2	10	6	
			40	22	17	-	18	6900ZZ×2	10	6	
			15	11	9	-	23	685ZZ×2	5	5	
			20	16	14	-	23	688ZZ×2	8	6	
			25	19	17	-	23	698ZZ×2	8	6	
			30	19	17	-	23	698ZZ×2	8	6	
			40	26	23	-	23	6000ZZ×2	10	8	
	21	20	50	28	25	-	23	6001ZZ×2	12	8	
			15	11	9	-	29	685ZZ×2	5	5	
			20	16	14	-	29	688ZZ×2	8	6	
			25	19	17	-	29	698ZZ×2	8	6	
			30	19	17	-	29	698ZZ×2	8	6	
			40	26	23	-	29	6000ZZ×2	10	8	
50			28	25	-	29	6001ZZ×2	12	8		
27			20	15	11	9	-	34	685ZZ×2	5	5
	20	16		14	-	34	688ZZ×2	8	6		
	25	19		17	-	34	698ZZ×2	8	6		
	30	19		17	-	34	698ZZ×2	8	6		
	40	26		23	-	34	6000ZZ×2	10	8		
	50	28		25	-	34	6001ZZ×2	12	8		
	32	20		15	11	9	-	34	685ZZ×2	5	5
				20	16	14	-	34	688ZZ×2	8	6
25			19	17	-	34	698ZZ×2	8	6		
30			19	17	-	34	698ZZ×2	8	6		
40			26	23	-	34	6000ZZ×2	10	8		
50			28	25	-	34	6001ZZ×2	12	8		



型号(①代码·②D) - ③T (FC·KLC·KFC·TC)
CDGB15 - 6 - KFC

可选加工 代码	法兰切削 FC	单侧切削法兰 KLC	单侧无法兰 KFC	变更法兰厚度 TC
技术说明	<p>切割法兰, 降低高度。 FC: 指定单位0.5mm</p> <p>① D ≤ FC < D+4 [指定方法] FC30.5 ② 圆弧型不适用</p>	<p>降低单侧法兰高度。 ① 圆弧型不适用 ② 不可与追加加工KFC并用</p>	<p>去除图中右侧的法兰。 ① 圆弧型不适用 ② 不可与追加加工KLC并用 ③ 指定切削法兰与单侧无法兰时, 请同时使用FC与KFC。</p>	<p>将法兰厚度加工为0.5, L尺寸缩短1mm。</p> <p>① 圆弧型不适用</p>