


1 代码 2 D — 3 公称型号
FFTE4

■ 请按步骤 1 ~ 3 选择型号和参数后进行订购。

型号区分:
代码 5 天发货



■ 45°接头

FFEFE 螺纹部: C3604(黄铜)
: 无电解镀镍

材质: PBT

型号		3 公称型号	A	B	C	对边距离 H	螺纹尺寸 M	有效截面积 (mm²)	重量(g)
1 代码	2 D								
FFEFE	4	1	17.1	16.3	9	10	R1/8	4.4	6.5
		2	17.1	19.3		14	R1/4		14.5
		M5	18.0	13.7		9	M5X0.8		5
	6	1	18.0	16.9	11.2	10	R1/8	8.5	7.5
		2	18.0	19.9		14	R1/4		15
		3	18.0	20.9		17	R3/8		24
	8	1	23.6	17.5	13.6	10	R1/8	15.0	8
		2	23.6	20		14	R1/4		15
		3	23.6	21		17	R3/8		23
	10	1	25	19.6	16.3	17	R1/8	22.1	18
		2	25	22.6		17	R1/4		22
		3	25	22.1		17	R3/8	31.5	23
		4	25	25.1		21	R1/2		39.5
	12	2	32.2	24.1	19.7	17	R1/4	41.7	27
		3	32.2	23.6		17	R3/8		28
		4	32.2	26.6		21	R1/2	42.6	44.5

■ 三通接头

FFTE 螺纹部: C3604(黄铜)
: 无电解镀镍

材质: PBT

型号		L1	L2	L3	B	C	G	F	P	对边距离 H	螺纹尺寸 M	重量(g)
1 代码	2 D											
FFTE	4	18.6	11.8	17.8	14.5	9	2.5	18.3	9.3	8	M5×0.8	7.4
	6	22	14.5	26.5	15.5	11.2	2.5	22.6	13	13	R1/8	18.5
	8	28.1	18	34	17.8	13.6	3	27.8	17	17	R1/4	35
	10	27.5	18	34	19.4	16.3	3	33.3	17	17	R1/4	57.5
	12	34.9	22	44.8	22.4	19.7	5	39.7	20	24	R1/2	98

■ 规格

使用流体	空气
使用温度范围 *	0~60℃
最高使用压力	0.9MPa
使用真空压力	-100kPa



邮箱: Service@srdfaa.com



传真: 0755-8957-5523

SRD仕瑞达