



型号(1代码·2T)  
ECM0.01

■ 请按步骤1~2选择型号和参数后进行订购。



型号区分:

代码

7天发货

■ 垫片卷



代码	W	长度	材质	硬度
ECM	12.7	1m	T=0.005、0.015 ... SUS304H	370~420HV
ECMW	45.0			
ECML	12.7	5m	T=0.01、0.02~0.5 ... SK材质	480~600HV
ECGSM	12.7			
ECGSMW	45.0	1m	SUS304H	370~420HV
ECGSML	12.7			



■ 标准型(长度1m)

型号	2 T	T公差	
1 代码	0.005	±0.0005	
	0.01	±0.003	
	0.015		
	0.02		
	ECM ECGSM (W=12.7mm)	0.03	±0.005
		0.04	
		0.05	
		0.06	
		0.07	
		0.08	
0.09			
0.1			
0.15			
0.2			
ECMW ECGSMW (W=45.0mm)	0.25	±0.015	
	0.3		
	0.35		
	0.4		
	0.45		
	0.5		

■ 加长型(长度5m)

型号	2 T	T公差	
1 代码	0.005	±0.0005	
	0.01	±0.003	
	0.015		
	0.02		
	ECML ECGSML (W=12.7mm)	0.03	±0.005
		0.04	
		0.05	
		0.06	
		0.07	
		0.08	
0.09			
0.1			
0.15			
0.2			
	0.2	±0.015	

