



型号(1)代码·(2)D公差·(3)D — (4)L
DAJTSLM5 — L12

■请按步骤①~④选择型号和参数后进行订购。



型号区分: 7天发货

直杆球面型 内螺纹型	材质	硬度	表面处理
DAJTSL	SUS304	镀层硬度850HV~	镀硬铬, 镀层厚度3~5μm
DAJLRL	SUJ2	淬火硬度HRC56~, 镀层硬度850HV~	镀硬铬, 镀层厚度3~5μm

DAJTSL
DAJLRL

①SUS440C材质的D部加工有识别槽。

■公差选择

D	M	P	G	H
	m6	p6	g6	h7
1~3	+0.008 +0.002	+0.012 +0.006	-0.002 -0.008	0 -0.010
4~6	+0.012 +0.004	+0.020 +0.012	-0.004 -0.012	0 -0.012
8~10	+0.015 +0.006	+0.024 +0.015	-0.005 -0.014	0 -0.015

定位销
夹具衬套

20

型号			(4)L	M	V
(1)代码	(2)D公差	(3)D	最小单位0.1		
DAJTSL	M(m6)	5	10.0~32.0	M2	3
DAJLRL	P(p6)	6		M3	5
	G(g6)	8		M5	8
	H(h7)	10	15.0~42.0	M5	8

型号(1)代码·(2)D公差·(3)D — (4)L — (DB...DH)
DAJTSLM5 — L12 — DC

代码	技术说明																														
DB	<p>增加引导部</p> <p>引导部D^{-0.01}_{-0.03}</p>	<p>选型方法 DB</p> <p>适用于D2以上规格</p>																													
DC	<p>增加排气槽</p> <p>D-0.15</p>	<p>选型方法 DC</p>																													
MA	<p>增加内螺纹</p> <p>MA</p> <p>E1</p>	<p>选型方法 MA</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>D</th> <th>MA</th> <th>E1</th> </tr> </thead> <tbody> <tr> <td>6</td> <td>M3</td> <td>4</td> </tr> <tr> <td>8-10</td> <td>M4</td> <td>6</td> </tr> </tbody> </table> <p>①不适用D6以下规格 ②仅适用于直杆锥型 标准型</p>	D	MA	E1	6	M3	4	8-10	M4	6																				
D	MA	E1																													
6	M3	4																													
8-10	M4	6																													
DM DP DG DH	<p>变更外侧公差</p> <p>L1±0.3</p> <p>L</p>	<p>选型方法 DM10</p> <p>变更L1尺寸的外径公差。</p> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th rowspan="2">D</th> <th colspan="4">公差代码</th> </tr> <tr> <th>DM</th> <th>DP</th> <th>DG</th> <th>DH</th> </tr> <tr> <td></td> <td>m6</td> <td>p6</td> <td>g6</td> <td>h7</td> </tr> </thead> <tbody> <tr> <td>1~3</td> <td>+0.008 +0.002</td> <td>+0.012 +0.006</td> <td>-0.002 -0.008</td> <td>0 -0.010</td> </tr> <tr> <td>4~6</td> <td>+0.012 +0.004</td> <td>+0.020 +0.012</td> <td>-0.004 -0.012</td> <td>0 -0.012</td> </tr> <tr> <td>8~10</td> <td>+0.015 +0.006</td> <td>+0.024 +0.015</td> <td>-0.005 -0.014</td> <td>0 -0.015</td> </tr> </tbody> </table> <p>①选型时请将L1尺寸变更为DM(DP/DG/DH)。</p>	D	公差代码				DM	DP	DG	DH		m6	p6	g6	h7	1~3	+0.008 +0.002	+0.012 +0.006	-0.002 -0.008	0 -0.010	4~6	+0.012 +0.004	+0.020 +0.012	-0.004 -0.012	0 -0.012	8~10	+0.015 +0.006	+0.024 +0.015	-0.005 -0.014	0 -0.015
D	公差代码																														
	DM	DP	DG	DH																											
	m6	p6	g6	h7																											
1~3	+0.008 +0.002	+0.012 +0.006	-0.002 -0.008	0 -0.010																											
4~6	+0.012 +0.004	+0.020 +0.012	-0.004 -0.012	0 -0.012																											
8~10	+0.015 +0.006	+0.024 +0.015	-0.005 -0.014	0 -0.015																											

邮箱: Service@srdfaa.com

传真: 0755-8957-5523

SRO仕瑞达

1052