



定位导向零件

调整螺钉支架 六角型 螺栓型

新增



型号(①代码·②M) — ③L
DBBATH3 — 10

■请按步骤①~③选择型号和参数后进行订购。





型号区分: 7 天发货
代码

■ 六角型



代码	类型	螺纹	材质	表面处理
DBBATH	六角型	粗牙	SS400	发黑
DBBBTN			SUS303	无电解镀镍
DBBCS		细牙	SS400	发黑
DBBDTH			SUS303	—
DBGVS				







型号		③L 选择	L ₁	M×螺距		d ₁	d ₂	t	B	(C)
①代码	②M			粗牙螺纹	细牙螺纹					
粗牙 DBBATH DBBBTN DBBCS 细牙 DBBDTH DBGVS	3	10 15 20	4	3×0.5	—	6.5	3.5	3	13	15
	4	15 20 25	5	4×0.7	4×0.5	8	4.5		14	16.2
	5	15 20 25 30	6	5×0.8	5×0.5	9.5	5.5		17	19.6
	6	20 25 30 35	7	6×1.0	6×0.75	11	6.5	5	19	21.9
	8	20 25 30 35	9	8×1.25	8×0.75	14	8.5		24	27.7
	10	25 30 35 40	10	10×1.5	10×1.0	17	10.5		30	34.6

■ 螺栓型



代码	类型	螺纹	材质		表面处理	附件	
			国标	相当		材质	表面处理
DBBFTH	螺栓型	粗牙	Q235	SS400	发黑	SS400	铬酸盐光泽处理
DBBGTH			Y1Cr18Ni9	SUS303	无电解镀镍	SUS304相当	—
DBBHS		细牙	Q235	SS400	—	SS400	铬酸盐光泽处理
DBBJTH					发黑	SS400	铬酸盐光泽处理



型号		③L 选择	M×螺距		N	E	P	D	F	(V)	B	T	(C)
①代码	②M		粗牙螺纹	细牙螺纹									
粗牙 DBBFTH DBBGTH DBBHS 细牙 DBBJTH	3	10 15 20	3×0.5	—	3	6	3	7	5.5	1	5.5	2.4	6.4
	4	10 15 20 25	4×0.7	4×0.5	4	8	4	8	7	1.4	7	3.2	8.1
	5	10 15 20 25 30	5×0.8	5×0.5	5	10	5	10	8	1.6	8	4	9.2
	6	15 20 25 30 35 40	6×1.0	6×0.75	6	12	6	12	10	2	10	5	11.5
	8	15 20 25 30 35 40	8×1.25	8×0.75	8	16	8	16	13	2.5	13	6.5	15
	10	20 25 30 35 40 50	10×1.5	10×1.0	10	20	10	22	17	3	17	8	19.6

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613