



齿轮/齿条



直齿轮

压力角20° 模数1.0



型号 (1 代码 · 2 模数) — 3 齿数 — 4 厚度B — 5 齿轮形状 — 6 轴径

CFAHB1.0

20

10

A

8

■ 请按步骤①~⑥选择
型号和参数后进行订购。



型号区分:

代码


7 天发货

A形状



代码		材质	表面处理
圆孔	键槽		
CFAHB	CFAKB	S45C	—
CFAHBB	CFAKBB		发黑
CFAHBG	CFAKBG		无电解镀镍
CFAHS	CFAKS		—
		SUS304	—

5 A 形



轴孔规格	
圆孔	键槽孔

① 未指定齿轮形状时, 齿数12~18为K形状, 齿数19~120为B形状。

型号		③ 齿数	④ 厚度B	⑤ 齿轮形状	⑥ 轴孔直径Ph7 最小单位1mm		d 基准圆 直径	D 齿顶圆 直径	G 齿根圆 直径			
① 代码	② 模数				圆孔	键槽孔						
圆孔	1.0	14	10	A	6~10 · 6.35	—	14	16	11.5			
		15			15		17	12.5				
		16			6~12		16	18	13.5			
		18					18	20	15.5			
		19			8~10	8N	19	21	16.5			
		20			6~10 · 6.35		20	22	17.5			
22		12	6~12 · 6.35		8N · 10N	22	24	19.5				
24						24	26	21.5				
25						25	27	22.5				
26						6~15 · 6.35	8N · 10N~12N	26	28	23.5		
28			8~17		10N~12N	28	30	25.5				
30			8~18		10N~15N	30	32	27.5				
32		8~18	32			34	29.5					
34		10	8~22			10N~17N	34	36	31.5			
35							35	37	32.5			
36					36		38	33.5				
40					40		42	37.5				
42					42		44	39.5				
45					45		47	42.5				
48		10	8~32		10N~30N	48	50	45.5				
50						8~34	10N~32N	50	52	47.5		
52								52	54	49.5		
60								10~38	12N~36N	60	62	57.5
70										70	72	67.5
72										72	74	69.5
80		10~48	12N~46N		80					82	77.5	
(① 齿数19以上)												



型号 (1 代码 · 2 模数) — 3 齿数 — 4 厚度B — 5 齿轮形状 — 6 轴径 — (etc)

CFAHB1.0

40

10

A

10

KTC25-K4

可选加工	台阶孔	两端台阶孔	侧面腰形孔
代码	DHL · DHR	WDH	LFC · LTC
技术说明	初始B形状 (可为A形) 	初始A形状 	LFC(腰形孔4处) 30° R=C/2 LTC(腰形孔3处) 30° R=C/2
可选加工	侧面通孔	侧面螺孔	侧面沉孔
代码	KFC · KTC	QFC · QTC	ZFC · ZTC
技术说明	KFC(通孔4处) KTC(通孔3处) 	QFC(螺孔4处) QTC(螺孔3处) 	(4处) ZFC (3处) ZTC

询价④种方式



官网 <http://www.srdfaa.com>
深圳市仕瑞达自动化设备有限公司



全国免费 400-966-3863
客服热线 0755-27926613